

Die Cast Aluminum



Die Cast Aluminum Half Blast Gate

- Designed for use with existing duct systems
- Galvanized steel slide w/ locking screw
- Simply cut a 3/8 inch slot halfway through pipe for blade insertion
- Commonly used for air balancing as well as a cut-off damper
- Maximum temperature 400° F
- Available in sizes 3" to 20"

DIE CAST ALUMINUM HALF BLAST GATE

DIA	PART #	A I.D.	B	C	D	E	F	BLADE GA.	WT.	PRICE
3"	BGH03	3.06	4.04	4.22	2.24	1.15	0.40	18	0.6	\$17.36
4"	BGH04	4.06	4.65	5.30	2.46	1.31	0.40	18	1.0	\$19.63
5"	BGH05	5.06	4.34	6.04	2.52	1.07	0.40	18	1.2	\$25.00
6"	BGH06	6.06	6.94	7.13	2.58	1.09	0.40	18	1.6	\$27.16
7"	BGH07	7.06	7.56	8.24	2.32	0.96	0.40	18	2.0	\$39.04
8"	BGH08	8.60	7.75	9.26	2.58	1.05	0.48	18	2.6	\$40.32
9"	BGH09	9.06	8.63	11.26	2.74	1.13	0.48	18	3.2	\$55.12
10"	BGH10	10.60	8.94	11.94	2.75	1.17	0.48	18	3.8	\$63.14
12"	BGH12	12.06	9.94	13.32	3.06	1.29	0.48	18	4.6	\$87.12
14"	BGH14	14.06	11.38	16.31	4.20	1.80	0.60	18	7.8	\$130.38
16"	BGH16	16.06	12.31	18.25	4.14	1.80	0.62	18	9.4	\$175.92
18"	BGH18	18.06	23.25	21.00	4.56	1.97	0.62	14	16.4	\$418.91
20"	BGH20	19.06	25.94	23.38	4.78	2.08	0.07	14	25.8	\$503.42

